

simply smart.



Pipe end processing machine

TUBOFORM A



Basic equipment and features

- Compact and rugged table-top machine for axial pipe end forming
- Hydraulic clamping for safe fixation of the pipe during the forming process
- Custom-designed and application-specific tooling (forming punch and clamping jaws)
- Precise adjustment of the pipe stop by means of a control dial with digit roller display
- High efficiency due to low cycle times
- Short set-up times for tooling
- Protective cover with safety switch
- Operator-friendly and easy to service

Additional features, options and accessories

- Foot switch for triggering the forming process
- Lubrication system

Models

- TUBOFORM A3 / TUBOFORM A5



Precise adjustment of the pipe stop.



Application examples: high-precision flaring of brake-lines, beading of hose connections.

Technical data	TUBOFORM A3	TUBOFORM A5
Pipe diameter range	Ø 3 - 12 mm	Ø 3 - 20 mm
Forming force (max.)	25 kN	60 kN
Clamping force (max.)	25 kN	60 kN
Stroke of the forming punch (max.)	30 mm	40 mm
Dimensions, approx. (WxHxD)	740 x 370 x 650 mm	740 x 430 x 710 mm
Weight, approx.	92 kg	98 kg
Connected load	1.7 kW	1.7 kW

Photos, text and illustrations are subject to change.
© TRACTO-TECHNIK GmbH & Co.KG. 2016-09.

